



SupraTech X
Woven for Performance. Built to Last.

TECHNICAL DATA SHEET

WOVEN CAPPED NEEDLE PUNCHED

SR NO.	TECHNICAL PARAMETER	STANDARD	TYPICAL VALUES
1	AREA WEIGHT (GSM)	ASTM D 5261	170 GSM
2	TENSILE STRENGTH	ASTM D 4632	110 x 100 LBS
3	ELONGATION AT BREAK	ASTM D 4632	15%
4	TRAPAZOID TEAR	ASTM D 4533	40 x 40 LBS
5	CBR PUNCTURE	ASTM D 6241	350 LBS
6	UV STABILITY	ASTM D 4355	70% @ 2500 HRS
7	AVAILABLE COLOURS	BLACK	
8	MARKING	STRIPES	
9	STANDARD WIDTHS	3ft - 17.5ft (Folded & Flat)	
10	STANDARD LENGTH	250ft - 2500ft	
11	PACKING	Polyliner & Stretch Wrapped	
12	MESH	AS PER REQUIREMENT	

- Above technical data are mean values based on production and independent institute tests for guidance only.
- There can be a tolerance of 10% in the above test result except weight.

The information given in this data sheet is based on tests conducted at our in-house laboratory and independent accredited laboratories. While the information is presented as a true and accurate representation of the attributes of the products to the best of our knowledge, no expressed or implied warranties are made and SupraTech X assumes no responsibility or liability with regard to the use of this information.

