



SupraTech X
Woven for Performance. Built to Last.

TECHNICAL DATA SHEET

PP WOVEN GROUND COVER

SR NO.	TECHNICAL PARAMETER	STANDARD	TYPICAL VALUES
1	AREA WEIGHT (GSM)	EN 965	90 GSM
2	TENSILE STRENGTH	EN ISO 10319	18 x 12 kN/M
3	ELONGATION AT BREAK	EN ISO 10319	18%
4	TRAPAZOID TEAR	ASTM D 4533	70 x 70 LBS
5	CBR PUNCTURE	EN ISO 12236	1900 N
6	UV STABILITY	ASTM D 4355	650 kly
7	AVAILABLE COLOURS	BLACK/WHITE/GREEN/BROWN	
8	MARKING	STRIPES OR GRIDS	
9	STANDARD WIDTHS	0.80m - 5.35m (Folded & Flat)	
10	STANDARD LENGTH	100m - 1000m	
11	PACKING	Polyliner & Stretch Wrapped	
12	MESH	AS PER REQUIREMENT	

- Above technical data are mean values based on production and independent institute tests for guidance only.
- There can be a tolerance of 10% in the above test result except weight.

The information given in this data sheet is based on tests conducted at our in-house laboratory and independent accredited laboratories. While the information is presented as a true and accurate representation of the attributes of the products to the best of our knowledge, no expressed or implied warranties are made and SupraTech X assumes no responsibility or liability with regard to the use of this information.

